

3rd **International Conference on Road and Rail Infrastructure** 28–30 April 2014, Split, Croatia

Road and Rail Infrastructure III

STATISTICS OF ST

Stjepan Lakušić – EDITOR

mmmm

Organizer University of Zagreb Faculty of Civil Engineering Department of Transportation

mmmmm



CETRA²⁰¹⁴ 3rd International Conference on Road and Rail Infrastructure 28–30 April 2014, Split, Croatia

TITLE Road and Rail Infrastructure III, Proceedings of the Conference CETRA 2014

еDITED BY Stjepan Lakušić

ISSN 1848-9850

PUBLISHED BY Department of Transportation Faculty of Civil Engineering University of Zagreb Kačićeva 26, 10000 Zagreb, Croatia

DESIGN, LAYOUT & COVER PAGE minimum d.o.o. Marko Uremović · Matej Korlaet

PRINTED IN ZAGREB, CROATIA BY "Tiskara Zelina", April 2014

COPIES 400

Zagreb, April 2014.

Although all care was taken to ensure the integrity and quality of the publication and the information herein, no responsibility is assumed by the publisher, the editor and authors for any damages to property or persons as a result of operation or use of this publication or use the information's, instructions or ideas contained in the material herein.

The papers published in the Proceedings express the opinion of the authors, who also are responsible for their content. Reproduction or transmission of full papers is allowed only with written permission of the Publisher. Short parts may be reproduced only with proper quotation of the source.

Proceedings of the 3rd International Conference on Road and Rail Infrastructures – CETRA 2014 28–30 April 2014, Split, Croatia

Road and Rail Infrastructure III

EDITOR Stjepan Lakušić Department of Transportation Faculty of Civil Engineering University of Zagreb Zagreb, Croatia **CFTRA**²⁰¹⁴ 3rd International Conference on Road and Rail Infrastructure 28-30 April 2014, Split, Croatia

ORGANISATION

CHAIRMEN

Prof. Stiepan Lakušić, University of Zagreb, Faculty of Civil Engineering Prof. Željko Korlaet, University of Zagreb, Faculty of Civil Engineering

ORGANIZING COMMITTEE

Prof. Stiepan Lakušić Prof. Želiko Korlaet Prof. Vesna Dragčević Prof. Tatiana Rukavina Assist, Prof. Ivica Stančerić dr. Maia Ahac Ivo Haladin dr. Saša Ahac losipa Domitrović Tamara Džambas

All members of CETRA 2014 Conference Organizing Committee are professors and assistants of the Department of Transportation, Faculty of Civil Engineering at University of Zagreb.

INTERNATIONAL ACADEMIC SCIENTIFIC COMMITTEE

Prof. Vesna Dragčević, University of Zagreb Prof. Isfendiyar Egeli, Izmir Institute of Technology Prof. Rudolf Eger, RheinMain University Prof. Ešref Gačanin, Univeristy of Sarajevo Prof. Nenad Gucunski, Rutgers University Prof. Libor Izvolt. University of Zilina Prof. Lajos Kisgyörgy, Budapest University of Technology and Economics Prof. Željko Korlaet, University of Zagreb Prof. Zoran Krakutovski, University of Skopie Prof. Stjepan Lakušić, University of Zagreb Prof. Dirk Lauwers. Ghent University Prof. Zili Li, Delft University of Technology Prof. Janusz Madejski, Silesian University of Technology Prof. Goran Mladenović, University of Belgrade Prof. Otto Plašek, Brno University of Technology Prof. Vassilios A. Profillidis, Democritus University of Thrace Prof. Carmen Racanel, Technical University of Civil Engineering Bucharest Prof. Tatiana Rukavina, University of Zagreb Prof. Andreas Schoebel, Vienna University of Technology Prof. Mirjana Tomičić-Torlaković, University of Belgrade Prof. Audrius Vaitkus, Vilnius Gediminas Technical University Prof. Nencho Nenov, University of Transport in Sofia

Prof. Marijan Žura, University of Ljubljana



FACTORS INFLUENCING DRIVER'S BEHAVIOUR AT INTERSECTIONS CROSSED BY THE TRAM

Fatiha Moutchou¹, Abdelghani Cherkaoui¹, El Miloudi El Koursi²

1 Mohammadia School of Engineering, Morocco 2 The French institute of science and technology for transport, development and networks, France

Abstract

Drivers' behaviour in intersections crossed by the tram is not only influenced by the rules of the tramway priority in the intersection but also by the road features that influence right or wrong behaviour of the driver. The driver follows the road with expectation and orientation logic formed by his experience and recent perceptions. This means that the road has to be constructed accordingly, so as to be understood, perceptible and recognizable.

Our research was aimed at finding out, how, in the dynamics of driving in intersection crossed by the tram, do drivers perceive and identify road situations, change in them, and the regulating actions they imply. We consider the causes of driver's operational error as the first step in a chain of actions, which may proceed to unwanted events. This paper describe our methodology for the analysis of driver behavior in real driving conditions, involving two techniques: the observation and measurement of two intersections crossed by tram at Rabat city, which were selected according to the number of collision and related incidents that occurred there combined with an assessment of the driver's behaviour during a journey made from within the vehicle itself. The merits of such an approach are highlighted and the main results are discussed and interpreted

Keywords: human factor, cognition, intersection, tramway, road environment, representation and perception logic

1 Introduction

The modern tramway has resurfaced as the cure to today's urban transport problems such as pollution, road congestion and uneven access to transit. However trams at intersections often experience frequent and extended delays due to vehicles crossing the tram tracks. There is an increased potential for conflict between trams and vehicles at these locations and crashes are common. Indeed from 2011 to 2013, it was reported a total of 222 tram-involved crashes in Rabat city, 4 fatal, and 81 with serious injury consequences. Of these, 125 (56%) involved tram-to-vehicle collisions at intersection.

Statistical data prove that there is a need to conduct research about the influence of tramway and surrounding environment, (specifically at crossroads) on car drivers' behaviour; the focus remains on creating an environment that minimises likelihood of serious injury.

With this focus in mind, our study aim to allow a systematic sorting out of the different malfunctions which intervene in the genesis of unwanted event at intersections crossed by tram. It is particularly important to recognize that the drivers' behaviour in intersections crossed by the tram is not only influenced by the rules of the tramway priority in the intersection but also by the road features that influence right or wrong behaviour of the driver.

Our analysis is based on the human factors concept taking into consideration the triggers of the driver's reactions and patterns of behaviour, which may result in an accident or even near miss. The systematic study of driver behaviour in real driving conditions makes in our view a useful contribution for such analyses.

The following article first situate the human aspect involved in driving activity, then for the purposes of illustrating our approach, we will briefly discuss some research method and their interest for understanding the way drivers behave in the situations concerned, we present in the last part our experimental study to collect data on driver performance at intersections crossed by tram and the primary finding of our research

2 The driver's ability to understand the road intersections crossed by tram

In order to better understand how we function as drivers at intersections crossed by tram we first turn to Endsley's thoughts on how human operators have evolved during the evolution in interaction with the world. According to this author, situational awareness is the perception of elements in the environment within a volume of time and space, the comprehension of their meaning and projection of their status in the near future,[1]. Applying Endsley's model to the driving environment, the driver firstly perceives road situations. The driver then has to comprehend what they have perceived, by forming "a holistic picture of the environment, comprehending the significance of those objects and events". Finally, the driver takes this understanding, and projects into the near future, in order to take the most appropriate action [2]. Situation awareness plays a vital role in driving as in every dynamic decision making. So driver performance can be evaluated through three parameters: the information received, the interpretation of this information made and the decision taken. An explanation of inappropriate driver behaviour should be sought at each of the different levels of situation awareness.

2.1 Driver's perception of the road

The perception of the road environment, especially its hazards, would be expected to influence driving performance, [3, 4, 5]. There are various level of perception that depends on the stimulus and the task confronting a person. The most basic form of perception is simple detection; that is, determining whether a signal or target is present, [6]. According to the literature [3][7], perception is more than just sensations; it uses memory, classifications, comparisons, and decisions to transform sensory data to a conscious awareness of the environment. This means that through our senses we get an immediate perception of the road environment and what is about to happen around us and we are unconsciously adapting our actions to the road. The physical design of the road and its various parts is the most important source of information to the driver. Drivers perceive the road and the traffic conditions as a whole. In this way, the drivers are the most perceptive of the information they need the most. Indeed drivers seem to be equipped with a well-developed "skip function", they try to acquire messages on aspects of their surroundings that they believe are relevant while ignoring those without useful information. It is an active process that requires significant discipline, as well as knowing what to look for, when to look for it and why.

2.2 Expectation and representation

In the field of cognitive psychology, the notion of representation refers to the idea of internal model developed by the subject for dealing with complex situation. Our understanding is built by combining observations from the real world with knowledge and experience recalled from memory, [8, 9]

The driver follows the road with expectation and orientation logic, which was formed by his experience and recent perceptions [10]. Lunenfeld and Alexander [11] define expectancy as "a driver's readiness to respond to situations, events, and information in predictable and successful ways". The expectations are functional for the driver in the sense that they are an important prerequisite for well-adapted driver behaviour [7].

The driver's expectations, however, will be dysfunctional in case he encounters an unexpected traffic situation. When the driver has false expectations of the road and traffic conditions, this mean that he well have an image or idea of what it is to happen which is not in conformity with reality. Indeed the drivers get "confused" and surprised when the road and traffic conditions are not in line with their expectations. In a situation where prompt action is required, problems often occur because there is no enough time to take proper actions, which implies a high risk of missing important information and making wrong decisions, [12].

In order to meet the driver's expectations, roundabouts crossed by tram have to be recognisable, distinguishable, interpretable and safe. This means that they must be designed in a consistent and standardized manner.

2.3 Driver's ability to read the road and self-explaining road

In the road safety context, Salmon and al [13] argue that incompatibilities in situation awareness across road users lie at the root of conflicts between them. A malfunctioning road and traffic environment is identified by the fact that drivers do not behave as intended. A large occurrence of deviant behaviour then indirectly shows that the drivers misunderstood and were surprised by the road and the traffic environment. Because the driver's reaction characteristics cannot be changed, the attention should be focused on a self-explanatory road design.

Concepts such as "positive guidance"[11], "road readability" and "self explaining road" [14] all these terms have been applied to those road designs that communicate to the driver what type of roads they are, or that can be easily categorized by drivers as requiring specific kinds of driving behaviour. They seek to identify the relevant infrastructures features likely to provide a clear picture of the functionality of the road space: how to cross an intersection crossed by tram, who has priority, what kind of information can be expected and so on. Designing road environments that facilitate the 'connection' of different road users' situation awareness therefore seems to provide an appropriate way to reduce collisions between them.

These questions raised from this perspective have led us to formulate our general hypothesis of research, which can be defined as follows: Driver behaviour at tram crossroads will depends very much on what is seen or "not seen" by the driver, in the road scene and how he "reads" the situation. Our research aims to evaluate which expectations the drivers have to tram crossroads and how they drive on it.

3 Overview of research method

In order to do analysis on road traffic dealing with human behaviour, it is required a great amount of data. The range of methods typically used includes observations, questionnaire, verbal protocol analysis and experts (police, road engineers, etc). In depth analysis normally requires experimental observations or field observations with specific supporting equipments. The general rules regarding data collection are (a) not to rely on one source of information and (b) to beware of potentially misleading information.

For the purposes of illustrating our approach, we will briefly discuss some research method and their interest for understanding the way drivers behave in the situations concerned.

3.1 Observation

Observation consists of recording behaviour during task performed. The three main ways that observational data are collected are direct observation, indirect observation, and participant observation. These methods can be used in combination with each other in order to obtain a broader understanding of the task. According to Stanton [15], one of the main concerns with observation is the intrusiveness of the observational method. Observing people affects what they do; people observed can bias the results as they might perform an unrepresentative range of tasks; and the way in which the data are recorded could compromise the reliability and validity of the observational study. In planning observational studies, a researcher identifies the variables to be measured, the methods to be employed, and the observational time frame. [16] For our study, the observation was based on an analysis grid that we have developed to carry out the assessement, and to examine whether it would be possible to identify characteristics of intersection crossed by tram that coincide with a higer likelihood of unwanted events. To guide our choice of elements to be included in this grid, we were inspired by the work of Millot [17] taking care to adapt the reading points to our own field of study and to our specific questions, [18].

3.2 Verbal protocol analysis

Verbal protocol analysis (VPA) is a method which involves participants 'thinking aloud' as they perform a task. Verbal protocol analysis uses data from verbal transcripts to analyze the content there in. These transcripts could come from protocols gathered from recordings of live performance of the task. The transcript can be coded and analyzed at various levels of detail, from individual words, to phrases, to sentences, to themes [19]. Verbal protocol analysis has found use within human factors research as a means of gaining insight into the cognitive underpinnings of complex behaviors. Walker [20] has pointed out the importance of Verbal protocol analysis; he stated that" Within the context of exploring hypotheses and conducting studies in naturalistic settings, verbal protocol analysis can be extremely useful and has much to offer".

To take into account all of these characteristics and the construction of driving in connection with a given situation, we felt that it was essential for our study, to put drivers in real driving situations. The methodology used entailed making observation from within the car during driving on two intersections crossed by tram. At these intersections we consider the point of view of drivers on how they carried out the activity, in order to collect explanatory data on it. This technique enables driver to make comments about his behavior, especially as regards to the environmental conditions which influenced him and came into play in the various situations he encountered.

3.3 Interviews

The interview is one of the original methods for gathering general information, and it has been popularly applied across a range of fields. Interviews can be classified into 4 types of informal conversation, semi-structured, standard structured and focus group interviews, [21]. Greenberg [22] proffers the idea that the task analyst can discover what tasks people perform and develop task descriptions through observation and then validate the descriptions through interviews with the same people. Annett [23] argues that data collection should comprise observation and interviewing at the very least.

Based on the literature review above, a specially designed questionnaire was carried out for the purposes of our study. The questionnaire was composed of three parts. The first part of questionnaire concerns the driver characteristics (gender, age, level of education), the second part concerns information about the driving characteristics of the interviewee (driving

experience, yearly kilometers driven, etc) and the third part of questionnaire contains a basic questions on the road design, the meaning of road signs related to tram, behaviour of other road users, and general questions about the problems that drivers could be experiencing with the tramway crossroad.

4 Study methodology and preliminary findings

4.1 Validation

As a first step, a validation exercise was carried out to assess the feasibility of the methodology. Two crossroads (see figure 1 and figure 2) at Rabat city were selected according to the number of collision and related incidents that occurred there in the last three years from 2011 to 2013.

During the validation exercise, observations were carried out. This involved spending periods of time at each crossroads and observing the behaviour of users. A review of the physical aspects of each crossroad and its surrounding were made. An assessment of the driver's behaviour during a journey within the vehicle itself was also used. A detailed explanation of the driving process was provided by the drivers as they progressed through the sequence of each roundabout, after the journey, the participants were asked to answer a questionnaire with relevant questions about the scene in order to better determine their knowledge and their representations of the driving situations studied.

4.2 Preliminary findings

The following list highlights a number of human factors and design features at each crossroads that can have an influential role in unwanted events and contribute to unsafe conditions. The list can be supplemented by further observations and interviews:

(i) At crossroad Al MANSOUR place at Rabat



Figure 1 Tramway crossroad AL MANSOUR PLACE

- A high traffic volumes and pedestrians movement due to shops, this requires car drivers to be alert for pedestrians and tram approaching;
- A stop line is not demarcated, either with a white line or appropriate pavement marking, to attract the driver's attention and help drivers identify safe stopping location;
- Tramway signs are not always conspicuous due to their position relative to other signs;

- Many drivers indicated that unfamiliarity with the tramway crossroad or driving at night would make the maneuver more challenging;
- Parked cars before and after the tramway line may result in vehicle drivers slowing and being caught on the tracks while a tram approaches
- Non compliance with traffic signal encouraged sometimes by police due to problems of traffic congestion;
- The sequence of lights is believed to be confusing in whether the lights are functional or not; the waiting time is perceived to be too long for all car drivers interviewed, which can be considered as an agent for psychological stress.
- The crossing being completed without the necessary caution increases during rush hours and on working days;
- Text in association with trams signs can be hard to read due to car driver's speed;
- For many drivers there is no difference between all the roads signs related to tram and they just ignore these roads signs so they cannot understand what is expected for them to do.



(ii) At crossroad street IBN ROCHD

Figure 2 Tramway Crossroad Street IBN Rochd.

- At some locations there is considerable visual clutter from surrounding infrastructure, which can detract from the primary safety messages "give way to tramway" and "beware of tram";
- · Text in association with trams signs can be hard to read due to car driver's speed;
- Some users failed to fully understand the meaning for various trams signs and aren't aware of the rules and procedures for correctly using trams crossroads;
- Drivers can be distracted from scanning for trams while they seek an appropriate gap in traffic on main road;
- A stop line is not demarcated, either with a white line or appropriate pavement marking to help drivers identify safe stopping location;
- · Vehicles waiting or queuing across the tram tracks due to traffic congestion;
- The curvature of the intersection creates a difficult angle from which to observe on-coming trams;
- The desire to pick gaps generated by traffic platoons can result in crossing being completed without the necessary caution, indeed the amount of time the users expect to wait at trams crossroads may influence their risk taking behaviour;

5 Conclusion

The conclusions of the preliminary findings of our study has identified a number of problems associated with tramway crossroad and has explored some of the road design and human factors that contribute to the difficulties experienced by drivers at these intersections. Evidence has been found that at the intersections visited, road scene elements and traffic condition play a role in the difficulties that drivers encounter when crossig these intersections. It is clear that much further investigation is required on the causal factors of errors and on the implications that these driver errors have on tram crossroad safety.

The second stage of the study is now to address the relationship between the elements of the tram environment and types of driver errors; this work is on progress, with the aim to provide suggestions for minimizing potential conflict between cars and trams and for enhancing error tolerance at tramway crossroads.

References

- [1] Endsley, M. & Kaber, D.: Team Situation Awareness for Process Control Safety and Performance, Process Safety Progress, Vol. 17, No. 1, 1998.
- [2] Bailly, B.: Conscience de la situation des conducteurs : aspects fondamentaux, méthodes et application pour la formation des conducteurs, Thèse de doctorat, spécialité psychologie cognitive, Université LUMIERE Lyon 2, 2004.
- [3] Dewar, R.: The Role of Human Factors in Road Safety Audits, Proceedings of the 18th Canadian Multidisciplinary Road Safety Conference, Whistler, British Columbia, June 8-11, 2008.
- [4] Gugerty, L.: Situation awareness in driving, Handbook for driving simulation in engineering, medicine and psychology. Ed J.Lee, D.Fisher. CRC press
- [5] Grane, C.: Haptic perception, attention and effects on performance in driving context. Doctoral thesis. Lulea university of technology, 2012.
- [6] Sanders, M. & Mc Cornick, E.: Human factors in engineering and design, Seventh edition, Mc Graw-Hill, Inc.
- [7] Helmers, G.: Explanatory model for road user behaviour. Implications for the design of road and traffic environment, Nordic human factors guideline, January 2014.
- [8] Saad, F.: In depth analysis of interactions between drivers and the road environment, 4the workshop of international cooperation on theories and concepts in traffic safety (ICTCT), Vienna, pp. 65-79, 1991.
- [9] Norman, D.: some observations on mental models, In: Gentner D., Stevens, A., Mental Models, Hillsdale, New Jersey, London, 1983.
- [10] Human factors guidelines for safer road infrastructure, www.piarc.org, 01.01.2012.
- [11] Lunenfeld, H. & Alexander, G.:Human Factors in Highway Design andOperations, Journal of Transportation Engineerin g, pp. 149-158, 1984.
- [12] Weller, G. & Dietz, M.: Definition, comparison and evaluation of existing self-explaining road approaches in Europe, Deliverable N° 1, SWOV, June 2010.
- [13] Salmon, P. M., Young, K. L., Cornelissen, M.: Compatible cognition amongst road users: the compatibility of driver, motorcyclist, and cyclist situation awareness. Safety Science, 56, pp. 6-17, 2013.
- [14] Saad, F.: In depth analysis of interactions between drivers and the road environment. 4th workshop of international cooperation on theories and concepts in traffic safety (ICTCT), Vienna, pp. 65-79, 1991.
- [15] Stanton, N.: The psychology of task analysis today ,the handbook of task analysis for humancomputer interaction, edited by diane Diaper and Neville Stanton
- [16] Wickens C., Lee, J., Liu, Y. & Becker, S.: An introduction to human factor engineering, second edition, Person prentice Hall, 2004.

- [17] Millot, M.: Etude des liens complexes entre forme urbaine et insécurité routière, La collection rapports technique du CERTU, 2004.
- [18] Moutchou, F., Cherkaoui, A. & El Koursi, E.: Integrating human factors in the analysis of the interaction Tram-Car Drivers, 2nd International conference on road and rail infrastructure – CETRA 2012, 7–9 May 2012, Dubrovnik, Croatia, pp. 1093-1099.
- [19] Stanton, N.: Behavioral and cognitive methods ,the handbook of task analysis for human-computer interaction, edited by Diane Diaper and Neville Stanton
- [20] Walker, G.: Protocol verbal analysis ,the handbook of task analysis for human-computer interaction, edited by Diane Diaper and Neville Stanton
- [21] Le Thu Huyen: Risk analysis, driver behaviour and traffic safety at intersections in Motocycle-Dominated traffic flow, tuprints.ulb.tu-darmstadt, 2009.
- [22] Greenberg, S.: Working through task- centered system design, the handbook of task analysis for human-computer interaction, edited by diane Diaper and Neville Stanton
- [23] Annett, J.: Hierarchical task analysis, the handbook of task analysis for human-computer interaction, edited by Diane Diaper and Neville Stanton.